


CRYSTAL
GRANITE & MARBLE
PVT. LIMITED



REGD. OFFICE :
DYNAMIX HOUSE, YASHODHAM,
GEN. A. K. VAIDYA MARG, GOREGAON (E),
MUMBAI - 400 063, INDIA.
TEL : 91-22-2840 2304 / 2840 2305
FAX : 91-22-2840 2322
E-MAIL : cristal@vsnl.com

WORKS :
PLOT NO. K-5, ADDL. MIDC AREA,
KODOLI VILLAGE, DIST. SATARA-415004,
MAHARASHTRA, INDIA.
TEL : 91-2162-246 126 / 244 500
FAX : 91-2162-244 126
E-MAIL : str_cristal@sancharnet.in

ADMN. OFFICE :
41st KM., BANGALORE-MYSORE ROAD,
VILL. MADAPURA, RAMANAGARAM TALUK,
BANGALORE-571511, KARNATAKA, INDIA.
TEL : 91-080-7276249/50
FAX : 91-080-7273867 / 7271291
E-MAIL : cristal@blr.vsnl.net.in



TO, PRECIDOSE PUMPS & SYSTEMS
62/13, PHASE I,
NR. PATELS AIRTEMP,
GIDC VATRA, AHMEDABAD
GUJARAT - 382 445

PURCHASE ORDER

No : 260054 Date : 06/05/2006
Your Ref : PO-382 Date : 20/01/2005
Division : SLAB

Please supply the undermentioned goods subject to terms and conditions stated on the reverse

sr.no	Req No.	Description	Quantity	unit price	total Rs. p.
01		HIGH PRESSURE TRIPLEX PLUNGER MODEL - TRE-X-45-30 (DETAILS AS PER ANNEXURE - 1)	1.00 NOS	148000.00	148000.00
		DISCOUNT ALLOWED	20.00%	Less	29600.00
		C.S.T. 4 % AGAINST C FORM	4.00%		4736.00
		PACKING CHARGES	3.00%		3694.08
		CENTRAL EXCISE NIL AGAINST CT3			
					126830.08

Recommended spare seal kit
to be supplied along with pump

ED :- NIL
MST :- NIL
CST :- SAME AS ABOVE

DELIVERY BY : 26.05.2006

PAYMENTS TERMS :

20% ADVANCE & BAL 80% AGST DOC

10% Performance bank guarantee
to be submitted

DESPATCH TO :

Material Will be Despatch through
any suitable Transport.
TO 41ST KM BANGALORE MYSORE ROAD
MADAPURA VILLAGE, RAMNANGARAM TALUK,
DIST. BANGALORE

For CRYSTAL GRANITE & MARBLE PVT.LTD.


Sr. Vice President

1. PARTY, 2. ACCOUNTS, 3. PO FILE, 4. FACTORY, 5. PARTY FILE

CRYSTAL GRANITE & MARBLE PVT. LTD.

ANNEXURE - I

PURCHASE ORDER - 260054 dt 06.05.2005

TECHNICAL SPECIFICATION

CAPACITY IN LPM (RATED)	63
DISCHARGE PRESSURE (KG / SQ CM)	134
SUCTION PRESSURE (KG / SQ CM)	FLOODED
CONNECTIONS IN BSP - INLET	3/4 " BSP
CONNECTIONS IN BSP - OUT LET	1/2 " BSP
STROKE LENGTH IN MM	45
STROKE / MINUTE	700
PLUNGER DIA. IN MM	30

MATERIAL OF CONSTRUCTION

CYLINDER	316 SS
PLUNGER	316 SS - HARD FACE (45-50 HRC)
VALVE SEAT & VALVE	316 SS - HARD FACE (45-50 HRC)
GLAND PACKING	PTFE - ARAMIDE / CHEVERON TYPE
CRANK SHAFT	AUSTEMPERED DUCTILE IRON SUJITABLE FOR HIGH FATIGUE STRENGTH & ROTATION TORSION
CONNECTING ROD	CARBON STEEL (FORGED)
MAIN BODY	FG-260

DRIVE DETAILS

H.P /SPEED	25 / 1500
V / Hz / Ph	415 / 50 / 3

SUPPLY INCLUDES PRESSURE RELIEF VALVE, PRESSURE SWITCH, BASE, BELT, PULLEY, BELT GUARD, PULSATION DAMPENER, PRESSURE GUAGE (GLYCERIN FILLED), STRAINER, GUN, NOZZLE, UNLOADER VALVE & SPARE SEAL KIT.



R.P. SHETTY
SR VICE PRESIDENT - ACCOUNTS & FINANCE