



MODEL : PA

MODEL	PLUNGER DIAMETER (MM)	FLOW (LPM)	MAX. RATED PRESSURE Kg/Cm ²	STROKES PER MINUTE	MOTOR	INLET	OUTLET
PA-30	30	84	180	1000	40 Hp	1½"	1"
	30	81	170	970	40 Hp	1½"	1"
	30	60	170	710	30 Hp	1½"	1"
	30	52	160	615	25 Hp	1½"	1"
	30	42	170	500	20 Hp	1½"	1"
PA-33	33	102	150	1000	40 Hp	1½"	1"
	33	99	140	970	40 Hp	1½"	1"
	33	72	140	710	30 Hp	1½"	1"
	33	63	140	615	25 Hp	1½"	1"
	33	51	140	500	20 Hp	1½"	1"
PA-36	36	122	120	1000	40 Hp	1½"	1"
	36	118	120	970	40 Hp	1½"	1"
	36	87	120	710	30 Hp	1½"	1"
	36	75	115	615	25 Hp	1½"	1"
	36	61	110	500	20 Hp	1½"	1"
PA-40	40	107	100	710	30 Hp	1½"	1"
PA-45	45	93	110	620	30 Hp	1½"	1"
	45	134	100	710	40 Hp	1½"	1"
PA-50	45	118	90	620	30 Hp	1½"	1"
	50	166	80	710	40 Hp	1½"	1"
	50	145	70	620	30 Hp	1½"	1"
	50	117	75	500	25 Hp	1½"	1"



MODEL : PB

PB-18	18	30	500	1000	40 Hp	1"	¾"
	18	29	480	970	40 Hp	1"	¾"
	18	21	480	710	30 Hp	1"	¾"
	18	18	470	615	25 Hp	1"	¾"
	18	15	470	500	20 Hp	1"	¾"
PB-20	20	37	400	1000	40 Hp	1"	¾"
	20	36	380	970	40 Hp	1"	¾"
	20	26	390	710	30 Hp	1"	¾"
	20	23	380	615	25 Hp	1"	¾"
	20	19	380	500	20 Hp	1"	¾"
PB-22	22	45	320	1000	40 Hp	1"	¾"
	22	44	320	970	40 Hp	1"	¾"
	22	32	320	710	30 Hp	1"	¾"
	22	28	310	615	25 Hp	1"	¾"
	22	23	310	500	20 Hp	1"	¾"
PB-25	25	59	250	1000	40 Hp	1"	¾"
	25	57	240	970	40 Hp	1"	¾"
	25	42	250	710	30 Hp	1"	¾"
	25	36	240	615	25 Hp	1"	¾"
	25	30	240	500	20 Hp	1"	¾"



MODEL : PC

PC-12	12	10	1200	750	40 Hp	¾"	½"
	12	8	1200	620	30 Hp	¾"	½"
	12	7	1200	550	25 Hp	¾"	½"
	12	5	1200	415	20 Hp	¾"	½"
PC-14	14	14	1000	750	40 Hp	¾"	½"
	14	10	1000	550	30 Hp	¾"	½"
	14	8	1000	450	25 Hp	¾"	½"
	14	7	1000	350	20 Hp	¾"	½"
PC-16	16	18	750	750	40 Hp	¾"	½"
	16	13	750	550	30 Hp	¾"	½"
	16	10	750	450	25 Hp	¾"	½"
	16	8	750	350	20 Hp	¾"	½"

Red colour shows direct couple driven models and others are Belt & Pulley or Gear Box driven.