

Hand Operated Hydro Test Pumps



Model Selection Chart

Model	Plunger Dia (mm)	Size BSP	Working Pressure		Pressure Gauge Range (PSI)	Net Weight (Kgs)
			BAR	PSI		
PHP - 140	20	½"	35	500	800	14.4
			70	1000	1500	
			105	1500	2000	
			140	2000	3000	
PHP - 350	15		211	3000	5000	17.5
			350	5000	7000	
PHP - 1000	10		500	7000	10000	17.5
			705	10000	15000	
			1000	14500	20000	

❖ APPLICATION:

Made for hydraulic testing of all sort of equipments subjected to work under pressure. Handy portable as well as trolley mounted. Operates manually by one person.

❖ STANDARD ITEMS:

- M. S. Fabricated Pail 14 swg - 15 ltrs.
- Pressure Hose with Attachments
- S.S. Check Valve
- Brass Foot Valve with S.S. filters
- Pressure Gauge

PressureJet Systems Pvt. Ltd.

(An ISO 9001-2008 CERTIFIED COMPANY)

62/13, Phase-1, G.I.D.C. Vatva, Ahmedabad – 382445. Gujarat, India

Phone: + 91 – 79 – 25830762 / 25893868 / 32455727, Fax: +91-79-25897220

E-Mail: sales@pressurejet.com • URL: www.pressurejet.com