

High Pressure Plunger Pump - PB



Material of Construction

- **Pump Head:** - CF 8 (SS 304)
- **Plunger :** - Ceramic coating/Tungsten Carbide coating
- **Valve & Valve Seat:** - Stainless Steel
- **Plunger Seal:** - PTFE Aramide
- **Crank Shaft:** - S G Iron – Hardened & Ground
- **Pump Body:** - FG 260

Major Applications

- **Hydro Test**
- **Hydro blasting**
- **Tube cleaning**
- **Water Sand blasting**
- **Spraying & many more...**



PB Series Model Selection Chart

Model	SPM	Flow (LPM)	Max. Rated Pressure-kg/cm ² (MOTOR-HP)			
PB 18	950	30	500(40)	360(30)	-	270(20)
	730	22	480(30)	400(25)	320(20)	-
PB 20	950	35	390(40)	300(30)	245(25)	195(20)
	730	27	380(30)	315(25)	250(20)	190(15)
PB 22	950	43	320(40)	240(30)	200(25)	160(20)
	730	33	320(30)	260(25)	210(20)	160(15)
PB 25	950	55	240(40)	190(30)	155(25)	125(20)

Complete System Includes Following Accessories: Bare Pump, Electric Motor/Diesel Engine, Belt & Pulley/Gear Box, Pressure Regulating Valve, Safety Valve, Strainer, Pressure Gauge etc. Other accessories like Trolley, Starter, Cable, Control panel etc. can also be supplied as per specific requirements of client.

PressureJet Systems Pvt. Ltd.

(An ISO 9001-2008 CERTIFIED COMPANY)

62/13, Phase-1, G.I.D.C. Vatva, Ahmedabad – 382445. Gujarat, India

Phone: + 91 – 79 – 25830762 / 25893868 / 32455727, Fax: +91-79-25897220

E-Mail: sales@pressurejet.com • URL: www.pressurejet.com