

High Pressure Plunger Pump – T2



Material of Construction

- **Liquid end:** - CF 8 (SS 304)
- **Plunger :** - Ceramic coating/Tungsten Carbide coating /Hard Chrome
- **Valve & Valve Seat:** - Stainless Steel
- **Plunger Seal:** - PTFE Aramide
- **Crank Shaft:** - Forged Alloy Steel
- **Pump Body:** - FG 260

Major Applications

- **Hydro Test**
- **Transfer**
- **Injection**
- **Reverse Osmosis**
- **Process**
- **Cleaning & many more...**



T-2 Series Model Selection Chart

Model	SPM	Flow (LPM)	Max. Rated Pressure-Kg/cm2 (MOTOR-HP)		
T2-10-19	700	5	175 (3)	115 (2)	-
	950	6.5	175 (4)	130 (3)	-
T2-15-10	950	2	375 (3)	200 (2)	-
	950	1	500 (2)	-	-
T2-20-10	570	2	-	125 (1)	-
	950	3	250 (3)	160 (2)	80 (1)
T2-20-19	435	7	150 (3)	100 (2)	40 (1)
	610	9	150 (4)	110 (3)	-
	700	11	140 (5)	110(4)	85(3)
	820	12.5	-	80 (3)	-
T2-20-22	435	9	110 (3)	75 (2)	-
	700	14	110 (5)	90(4)	75 (3)
	820	17	100 (5)	80(4)	60 (3)
	950	19	90 (5)	72(4)	55 (3)
T2-30-22	950	29	55 (5)	40(4)	30 (3)
	820	25	65 (5)	50(4)	40 (3)
	435	13	55 (2)	-	-
T2-30-19	950	22	75 (5)	60(4)	45 (3)
	700	16	85 (4)	65 (3)	-
	435	10	70 (3)	45(2)	-

Complete System Includes Following Accessories: Bare Pump, Electric Motor/Diesel Engine, Belt & Pulley/Gear Box, Pressure Regulating Valve, Safety Valve, Strainer, Pressure Gauge etc. Other accessories like Trolley, Starter, Cable, Control panel etc. can also be supplied as per specific requirements of client.

PressureJet Systems Pvt. Ltd.

(An ISO 9001-2008 CERTIFIED COMPANY)

62/13, Phase-1, G.I.D.C. Vatva, Ahmedabad – 382445. Gujarat, India

Phone: + 91 – 79 – 25830762 / 25893868 / 32455727, Fax: +91-79-25897220

● E-Mail: sales@pressurejet.com ● URL: www.pressurejet.com