

## High Pressure Plunger Pump - TW-14.30



### Material of Construction

- **Liquid end:** - Nodular Graphite Cast Iron
- **Plunger :** - Chrome Plated Stainless Steel
- **Valve & Valve Seat:** - Stainless Steel
- **Plunger Seal:** - NBR
- **Crank Shaft:** - Forged
- **Pump Body:** - Aluminum Alloy Die Casting

### Major Applications

- **Hydro Test**
- **Industrial Cleaning**
- **Two Wheeler Washing**
- **Car Washing**
- **Spraying & many more...**



### Technical Data Chart

PARAMETER	DESCRIPTION
<b>Capacity Range</b>	Min. Flow rate 7 LPM (1.85 GPM) @ max. Pressure 35 Kg/cm <sup>2</sup> (497.82 PSI) Max. Flow rate 14 LPM (3.70 GPM) @ max. Pressure 35 Kg/cm <sup>2</sup> (497.82 PSI)
<b>Pump Speed Range</b>	500 TO 800 SPM
<b>Motor HP</b>	Up to 2 HP
<b>Transmission</b>	Belt/Gear Drive

**Complete System Includes Following Accessories:** Bare Pump, Electric Motor/Diesel Engine, Belt & Pulley, Unloader Valve, Pulsation Dampner, Strainer, Ball Valve, Pressure Gauge etc. Other accessories like Trolley, Starter, Cable, Control panel etc. can also be supplied as per specific requirements of client.

## **PressureJet Systems Pvt. Ltd.**

(An ISO 9001-2008 CERTIFIED COMPANY)

62/13, Phase-1, G.I.D.C. Vatva, Ahmedabad – 382445. Gujarat, India

Phone: + 91 – 79 – 25830762 / 25893868 / 32455727, Fax: +91-79-25897220

E-Mail: [sales@pressurejet.com](mailto:sales@pressurejet.com) • URL: [www.pressurejet.com](http://www.pressurejet.com)

## High Pressure Plunger Pump - TW-28.35



### Material of Construction

- **Liquid end:** - Nodular Graphite Cast Iron
- **Plunger :** - Chrome Plated Stainless Steel
- **Valve & Valve Seat:** - Stainless Steel
- **Plunger Seal:** - NBR
- **Crank Shaft:** - Forged
- **Pump Body:** - Aluminum Alloy Die Casting

### Major Applications

- **Hydro Test**
- **Industrial Cleaning**
- **Two Wheeler Washing**
- **Car Washing**
- **Spraying & many more...**



### Technical Data Chart

PARAMETER	DESCRIPTION
<b>Capacity Range</b>	Min. Flow rate 20 LPM (5.28 GPM) @ max. Pressure 35 Kg/cm <sup>2</sup> (497.82 PSI) Max. Flow rate 28 LPM (7.40 GPM) @ max. Pressure 35 Kg/cm <sup>2</sup> (497.82 PSI)
<b>Pump Speed Range</b>	500 To 800 SPM
<b>Motor HP</b>	Up to 2 HP
<b>Transmission</b>	Belt/Gear Drive

**Complete System Includes Following Accessories:** Bare Pump, Electric Motor/Diesel Engine, Belt & Pulley, Unloader Valve, Pulsation Dampner, Strainer, Ball Valve, Pressure Gauge etc. Other accessories like Trolley, Starter, Cable, Control panel etc. can also be supplied as per specific requirements of client.

## PressureJet Systems Pvt. Ltd.

(An ISO 9001-2008 CERTIFIED COMPANY)

62/13, Phase-1, G.I.D.C. Vatva, Ahmedabad – 382445. Gujarat, India

Phone: + 91 – 79 – 25830762 / 25893868 / 32455727, Fax: +91-79-25897220

E-Mail: [sales@pressurejet.com](mailto:sales@pressurejet.com) • URL: [www.pressurejet.com](http://www.pressurejet.com)